


# ACOUSTIC ALU

ASACA-GA-16



## ITEM SIZE (mm)

25 x 20

## GROOVE SIZE (mm)

25,1 x 20

## AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 -  
1230 - 1330 - 1430 - 1530

## MATERIALS

**EXTERNAL PROFILE** 6060 T6 aluminium alloy

**INTERNAL PROFILE** 6060 T6 aluminium alloy

**AVAILABLE FINISHING** Mill

**MECHANISMS** Nylon PA6 30% Fiberglass reinforced

**SEAL** GA. Sound-insulating seal in self-extinguishing thermoplastic. Color: Grey.

**CLOSING END-CAP** Included. Nylon PA6 30% Fiberglass reinforced. Color: black

**ACTIVATION PLUNGER** 16. Nylon plunger with rounded head adjustable with a 3 mm Allen wrench. Color: black

## TECHNICAL CHARACTERISTICS

**MAXIMUM DROP (mm)** 14

**WORKING TEMPERATURES (C°)** -20° / +80°

**FIXING TYPE** 2F. With pre-assembled screws (3,5x30 pan head (wood) or  
3,5x32 (steel) countersunk nickel plated screws) or  
1F. With stainless steel brackets (includes 3,5x20 countersunk nickel plated screws).

## CERTIFICATES

**WORKING CYCLES** > 200.000 (internal test)

**ACOUSTIC INSULATION** **50dB Rw** - Cert. n. PB-G03-04-en-01-PB01 - IFT Rosenheim

**FIRE RESISTANCE** /

**SMOKE TESTED** /



# ACOUSTIC ALU

ASACA-GA-16

| ITEM LENGTH<br>mm | ITEM WEIGHT<br>Kgs | BOX WEIGHT<br>Kgs | MAX TRIMMING<br>mm | TRIMMING from -> to<br>mm |
|-------------------|--------------------|-------------------|--------------------|---------------------------|
| 330               | 0,160              | 5,65              | 50                 | 330 -> 280                |
| 430               | 0,208              | 7,09              | 110                | 430 -> 320                |
| 530               | 0,257              | 8,56              | 150                | 530 -> 380                |
| 630               | 0,305              | 10,00             | 150                | 630 -> 480                |
| 730               | 0,353              | 11,44             | 150                | 730 -> 580                |
| 830               | 0,401              | 12,88             | 150                | 830 -> 680                |
| 930               | 0,449              | 14,32             | 150                | 930 -> 780                |
| 1030              | 0,497              | 15,76             | 150                | 1030 -> 880               |
| 1130              | 0,545              | 17,20             | 150                | 1130 -> 980               |
| 1230              | 0,593              | 18,64             | 150                | 1230 -> 1080              |
| 1330              | 0,641              | 20,08             | 150                | 1330 -> 1180              |
| 1430              | 0,689              | 21,52             | 150                | 1430 -> 1280              |
| 1530              | 0,737              | 22,96             | 150                | 1530 -> 1380              |
|                   |                    |                   |                    |                           |
|                   |                    |                   |                    |                           |
|                   |                    |                   |                    |                           |

## PACKAGING

**MINIMUM PACKAGING** 5 pieces

**BOX PACKAGING** 30 pieces

### ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.

