


EUREKA

ASEU-L-1



ITEM SIZE (mm)

10 x 18

GROOVE SIZE (mm)

10,1 x 18

AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 - 1230

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL L. Three lips mono-extruded soft thermoplastic seal. Color: black

CLOSING END-CAP Not included.

ACTIVATION PLUNGER 1. Self directing articulated metal plunger with nylon cap, adjustable with 3mm Allen wrench.
Nylon PA6 30% Fiberglass reinforced. Color: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 10

WORKING TEMPERATURES (C°) -20° / +80°

FIXING TYPE 4F. with pre-mounted nails.

CERTIFICATES

WORKING CYCLES > 200.000 (internal test)

ACOUSTIC INSULATION /

FIRE RESISTANCE /

SMOKE TESTED /



EUREKA

ASEU-L-1

ITEM LENGTH mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,095	6,40	50	330 -> 280
430	0,124	8,14	100	430 -> 330
530	0,153	9,88	150	530 -> 380
630	0,182	11,62	150	630 -> 480
730	0,211	13,36	150	730 -> 580
830	0,240	15,10	150	830 -> 680
930	0,269	16,84	150	930 -> 780
1030	0,298	18,58	150	1030 -> 880
1130	0,327	20,32	150	1130 -> 980
1230	0,356	22,06	150	1230 -> 1080

PACKAGING

- MINIMUM PACKAGING 10 pieces
- BOX PACKAGING 60 pieces

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.
Keep stored in a dry place, protected from water, solvents and direct sunlight.