



ITEM SIZE (mm)
20 x 11

GROOVE SIZE (mm)
20,1 x 12

AVAILABLE LENGTHS (mm)
330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 -
1230 - 1330 - 1430 - 1530 - 1630

MATERIALS

- EXTERNAL PROFILE** 6060 T6 aluminium alloy
INTERNAL PROFILE 6060 T6 aluminium alloy
AVAILABLE FINISHING Mill
MECHANISMS Shell type mechanism with steel springs.
SEAL S. Mono-extruded soft thermoplastic seal. Color: black
CLOSING END-CAP Not included.
ACTIVATION PLUNGER 7. Steel plunger, adjustable with slotted screwdriver.

TECHNICAL CHARACTERISTICS

- MAXIMUM DROP (mm)** 13
WORKING TEMPERATURES (C°) -20° / +80°
FIXING TYPE 3F. Removing the inner profile (screws not included).

CERTIFICATES

- WORKING CYCLES** > 200.000 (internal test)
ACOUSTIC INSULATION /
FIRE RESISTANCE /
SMOKE TESTED /

MEC

ASME-S-7

ITEM LENGTH mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,109	7,24	120	330 -> 210
430	0,142	9,22	180	430 -> 250
530	0,175	11,20	150	530 -> 380
630	0,208	13,18	150	630 -> 480
730	0,241	15,16	150	730 -> 580
830	0,274	17,14	150	830 -> 680
930	0,307	19,12	150	930 -> 780
1030	0,340	21,10	150	1030 -> 880
1130	0,373	23,08	150	1130 -> 980
1230	0,406	25,06	150	1230 -> 1080
1330	0,439	27,04	150	1330 -> 1180
1430	0,472	/	150	1430 -> 1280
1530	0,505	/	150	1530 -> 1380
1630	0,538	/	150	1630 -> 1480

PACKAGING

MINIMUM PACKAGING 10 pieces

BOX PACKAGING 60 pieces (except where noted)

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.

