


TOP PLUS

ASTPL-TA-1

**ITEM SIZE (mm)**

13 x 28

GROOVE SIZE (mm)

13,1 x 28

AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL T + A. Co-extruded seal in self-extinguishing thermoplastic. Color: grey

CLOSING END-CAP Included. Nylon PA6 30% Fiberglass reinforced. Color: black

ACTIVATION PLUNGER 1. Self directing articulated metal plunger with nylon cap, adjustable with 3mm Allen wrench.
Nylon PA6 30% Fiberglass reinforced. Color: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 18

WORKING TEMPERATURES (C°) -20° / +80°

FIXING TYPE 2F. With pre-assembled screws (3,5x20 countersunk nickel plated screws) or
1F. With stainless steel brackets (includes 3,5x20 countersunk nickel plated screws).

CERTIFICATES

WORKING CYCLES > 200.000 (internal test)

ACOUSTIC INSULATION **44dB Rw** - Cert. n. PB Z10-G03-04-en-01 - IFT Rosenheim

FIRE RESISTANCE /

SMOKE TESTED /



TOP PLUS

ASTPL-TA-1

ITEM LENGTH mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,139	7,70	50	330 -> 280
430	0,181	9,80	135	430 -> 295
530	0,223	11,90	200	530 -> 330
630	0,265	1,40	200	630 -> 430
730	0,307	16,10	200	730 -> 530
830	0,349	18,20	200	830 -> 630
930	0,391	20,30	200	930 -> 730
1030	0,433	22,40	200	1030 -> 830
1130	0,475	24,50	200	1130 -> 930

PACKAGING

- MINIMUM PACKAGING 5 pieces
- BOX PACKAGING 50 pieces

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.
Keep stored in a dry place, protected from water, solvents and direct sunlight.