
GLASS FRAME

GLASSFR10



ITEM SIZE (mm)

20,5 x 18,2

GLASS WIDTH (mm)

10

AVAILABLE LENGTHS (mm)

3000

MATERIALS —

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE /

AVAILABLE FINISHING Silver anodised, stainless steel, scotch brite, black anodised

MECHANISMS /

SEAL Internal: soft tubolar PVC. External: coextruded TPE

CLOSING END-CAP /

ACTIVATION PLUNGER /

TECHNICAL CHARACTERISTICS ——

MAXIMUM DROP (mm) /

WORKING TEMPERATURES (C°) -20° / +80°

FIXING TYPE /

CERTIFICATES -

WORKING CYCLES /

ACOUSTIC INSULATION /

FIRE RESISTANCE /

SMOKE TESTED /

GLASS FRAME

GLASSFR10

| ITEM LENGTH | ITEM WEIGHT Kgs | BOX WEIGHT Kgs | MAX TRIMMING mm | TRIMMING from -> to |
|-------------|--------------------|-------------------|--------------------|---------------------|
| 3000 | 1,000 | 10,40 | max | max |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

PACKAGING —

MINIMUM PACKAGING 10 pieces

BOX PACKAGING 10 pieces

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.